

NVR

32/64 CH NVR

12MP/8MP/6MP/5MP/4MP/3MP/1080P/720P HD NVR



TD-3500B8-P2

- 4K Output
- 8MP
- DDNS
- Network
- PTZ
- Audio
- MIC
- Mobile
- CMS
- USB
- Mouse
- E-mail
- STD
- FR
- VCA

TD-3500B8-P2 series supports 32 /64CH 12MP /8MP / 6MP /5MP / 4MP / 3MP / 1080P / 1280 × 1024 / 960P /720P high definition IP video input, which adopts the most advanced SOC technique to ensure high definition recording in each channel and realize outstanding robustness of the system.

TD-3500B8-P2 series supports 32/64 CHIP input, simultaneous 16 CH playback, and 4K high definition display. The series of products can meet different security requirements of home, financial, commerce, enterprise, transportation and government, etc.



en.tvt.net.cn

For more information, please visit our website

Shenzhen TVT DIGITAL TECHNOLOGY CO., LTD.

Address: 23rd Floor, Block B4, Building NO.9, Shenzhen Bay Eco-Technology Park, Nanshan District, Shenzhen, Guangdong Province, P.R.China

Tel: +86-755-36995888

Web site: <http://en.tvt.net.cn>

Fax: +86-755-33104777

E-mail: overseas@tvt.net.cn

SPECIFICATIONS

Model		TD-3532B8-P2	TD-3564B8-P2
System	OS		
Video	IP Video Input	32 CH IPC input	64 CH IPC input
	Incoming Bandwidth (Mbps)	320	640
	Outgoing Bandwidth (Mbps)	320	Display Priority: 128 Network Priority: 640
	IP Video Input Resolution	12MP/8MP/6MP/5MP/4MP/3MP/1080P/1280x1024/960P/720P/960H/D1/CIF	
	Output	HDMI1 : 3840 × 2160@60fps / 3840 × 2160@30fps/ 1920 × 1080 / 1280 × 1024 / 1024 × 768 HDMI2: 1920 × 1080 / 1280 × 1024 / 1024 × 768 HDMI3: 1920 × 1080 / 1280 × 1024 / 1024 × 768 HDMI4: 1920 × 1080 / 1280 × 1024 / 1024 × 768 VGA × 1 : 1920 × 1080 / 1280 × 1024 / 1024 × 768	
	Compression	Standard H.264/H.265/MJPEG	
Audio	Network Input	32 CH	64 CH
	2-way Audio	RCA × 1	
	Local Output	RCA × 1	
	HDMI Audio Output	Yes	
	Compression	G.711(U/A)	
Record	Record Stream	Dual stream recording	
	Resolution	12MP/8MP/6MP/5MP/4MP/3MP/1080P/1280x1024/960P/720P/960H/D1/CIF	
	Frame Rate	25fps (PAL) / 30fps(NTSC)	
	Mode	Manual, timer, motion, sensor, smart events	
Playback	Simultaneous Playback	Max 16 CH	
	Search	Time slice / time / event / tag search	
	Smart Search	Highlighted color to display the camera record in a certain period of time, different colors refers to different record events	
Decoding Capability	Live/Playback	1CH 12MP/4CH 5MP/9CH 720P/16CH 720P	
Alarm	Mode	Manual, sensor, motion, exception, smart events	
	Input	16 CH local alarm input; IPC alarm input supported	
	Output	4 CH	
Face	Face Detection Performance (AI by IPC)	32 CH	64 CH
	Face Detection Performance (AI by Device)	4CH	
	Face Match Performance	8 CH	16 CH
	Comparison Capability	48 pictures / second	36 pictures / second
	Face Picture Database	32 libraries 10000 Face Pictures	
	Face Picture Search	Search by picture is supported	
	Database Management	Add, modify, delete and search face pictures	
	Face Picture Adding	Add face pictures through APP, WEB and external import	
	External face picture enrollment	Resolution : 128 x 128 ~ 1920 x 1080 Size : less than 70KB Format : jpg, jpeg	
	Face Picture Comparison	Support common, allow list and block list alarm	
	Face Track	Yes	

Face	Map of Face Track	Resolution : ≤ 2960x1668 Size : ≤ 512KB Format : jpg, jpeg
	Statistic Graph of Face Information	Bar graph
	Statistic Mode of Face Information	Statistics by day, week, month, quarter as well as customized time period
Network	Interface	RJ45 10/100/1000Mbps(POE)×32
	Protocol	TCP/IP, PPPoE, DHCP, DNS, DDNS, UPnP, NTP, SMTP, SNMP, HTTP, HTTPS, RTSP, ONVIF, UDP, FTP, IPv4, IPv6
Mobile Device	OS	iOS, Andriod
Storage	HDD Interface	SATA × 8, max 10T per HDD; e-SATA × 1
	RAID Type	RAID0, 1, 5, 6, 10
Backup	Local Backup	U disk, USB mobile HDD
	Network Backup	Yes
Port	USB	USB2.0×1, USB3.0×2
	Remote Controller	Optional
	RS485/RS232	Yes (full-duplex), connect to PTZ or keyboard
Others	Power Supply	ATX700W
	Consumption	≤ 630W(withoutHDD)
	Dimensions	445mm×436mm×90mm
	Working Environment	-15 ~ 50 °C , Humidity: 10% ~ 90%

Features

- Support 32/64CH 12MP /8MP / 6MP / 5MP / 4MP / 3MP / 1080P / 1280 × 1024 / 960P / 720P IP input
- Standard H.265 high profile compression format to get high-quality video at much lower bit rate
- Intuitive and user-friendly Graphic User Interface (GUI), Windows style operation by mouse
- Multi-mode recording: manual / timer / motion / sensor/smart events
- Playback : 16 CH simultaneous playback
- Search : time slice, time, event, tag, smart and target database search
- Support face detection and comparison
- Support multiple VCA (Video Content Analytics) events, such as object abandoned/missing, region intrusion, tripwire, video tampering, etc.
- Support POS information overlay on live view and playback
- Support RAID0, 1, 5, 6, 10
- Express and flexible backup via USB, network and so on
- Pentaplex : preview, record, playback, backup and remote access
- DHCP, DDNS, PPPoE network protocol
- Compatible with third-party IPCs, such as ONVIF, Hikvision, etc.
- Remote control via Web Client or CMS : preview, playback, backup, PTZ and configuration
- Dual stream technology for local storage with high definition, remote network transmission and remote surveillance with mobile device
- Multi-user online simultaneously
- Authorization management, log view and device status view
- 4K output, true high resolution display
- Support PTZ preset and auto cruise, up to 255 presets and 8 cruises
- Support NAT function and QRCode scanning by mobile phones
- Powerful mobile surveillance by smart phones with iOS and Andriod OS